

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number  
WO 2004/011702 A1

- (51) International Patent Classification<sup>7</sup>: D01D 5/098 [KR/KR]; 212 Gongdan-dong, Gumi-si, Kyungsangbuk-do 730-030 (KR).
- (21) International Application Number: PCT/KR2003/001501
- (22) International Filing Date: 26 July 2003 (26.07.2003)
- (25) Filing Language: Korean
- (26) Publication Language: English
- (30) Priority Data:  
10-2002-0044170 26 July 2002 (26.07.2002) KR  
10-2002-0044173 26 July 2002 (26.07.2002) KR
- (71) Applicant (for all designated States except US): KOLON INDUSTRIES, INC. [KR/KR]; Kolon Tower, 1-23, Byulyang-dong, Kwacheon-city, Kyunggi-do 427-040 (KR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KIM, Yun-Jo [KR/KR]; 104-905 Hyundai APT, Bonggok-dong, Gumi-si, Kyungsangbuk-do 730-764 (KR). LEE, Su-Jin
- (74) Agent: CHO, Hwal-Rai; Suite No. 1507 Yoksam Heights Bldg, 642-19, Yoksam-Dong, Kangnam-Gu, Seoul 135-981 (KR).
- (81) Designated States (national): AE, AG, AL, AM, AU, AZ, BA, BB, BR, BY, BZ, CA, CN, CO, CR, CU, DM, DZ, EC, GD, GE, GH, GM, HR, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, RU, SC, SD, SG, SL, SY, TJ, TM, TN, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A HIGH STRENGTH LOW SHRINKAGE POLYESTER DRAWN YARN, AND A PROCESS OF PREPARING FOR THE SAME



(57) Abstract: The present invention discloses a high strength low shrinkage polyester drawn yarn used as industrial yarns and a process for producing the same. The strength low shrinkage polyester drawn yarn has a thermal relaxation stress change ratio of 5 to 100% and a thermal relaxation stress area ratio of 50 to 140% on a thermal relaxation and shrinkage stress curve with a final temperature set to 170°C. The process for producing a high strength low shrinkage polyester drawn yarn by a direct spin draw (DSD) process in which a quenching delay region I is mounted, wherein the high strength low shrinkage polyester drawn yarn is produced in such methods that a spinning oil is attached to the yarn being spun with an oiling apparatus 8 mounted at the position 500 to 1,500mm below from the lower bottom surface of the insulating board 3, the relaxation stress of the yarn is controlled with one or tow tension guides 9 mounted between Godet rollers of a relaxation region III, or both oiling apparatus 8 and tension guides 9 are mounted.

WO 2004/011702 A1